

ABSTRACT

In an electrostatic head, each of electrostatic actuators includes a diaphragm doubling as or including a
5 first electrode forming a wall surface of a discharge room communicating with a nozzle discharging a drop, and a second electrode opposing the first electrode. The diaphragm is deformed by generating an electrostatic force between the first electrode and the second electrode. The first
10 electrodes or the second electrodes of the electrostatic actuators are combined electrically. Differently polarized potentials are applied to the first electrode and the second electrode upon discharging the drop.

(19) World Intellectual Property
Organization
International Bureau



25 JAN 2005


(43) International Publication Date
1 April 2004 (01.04.2004)

PCT

(10) International Publication Number
WO 2004/026582 A1

- (51) International Patent Classification⁷: B41J 2/045, 2/055
- (72) Inventor; and
(75) Inventor/Applicant (*for US only*): TANAKA, Shinji [JP/JP]; 11-3-301, Kitayamata 3-chome, Tsuzuki-ku, Yokohama-shi, Kanagawa 224-0021 (JP).
- (21) International Application Number: PCT/JP2003/011851
- (74) Agent: ITOH, TADAHIKO; 32nd Floor, Yebisu Garden Place Tower, 20-3, Ebisu 4-chome, Shibuya-ku, Tokyo 150-6032 (JP).
- (22) International Filing Date: 17 September 2003 (17.09.2003)
- (25) Filing Language: English
- (81) Designated States (*national*): CN, KR, SG, US.
- (26) Publication Language: English
- (84) Designated States (*regional*): European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR).
- (30) Priority Data: 2002-272383 19 September 2002 (19.09.2002) JP
- Published: — with international search report
- (71) Applicant (*for all designated States except US*): RICOH COMPANY, LTD. [JP/JP]; 3-6, Nakamagome 1-chome, Ohta-ku, Tokyo 143-8555 (JP).
- For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*

(54) Title: HEAD DRIVE CONTROL DEVICE AND INKJET RECORDING DEVICE



(57) **Abstract:** In an electrostatic head, each of electrostaticactuators includes a diaphragm doubling as or including a first electrode forming a wall surface of a discharge room communicating with a nozzle discharging a drop, and a second electrode opposing the first electrode. The diaphragm is deformed by generating an electrostatic force between the first electrode and the second electrode. The first electrodes or the second electrodes of the electrostatic actuators are combined electrically. Differently polarized potentials are applied to the first electrode and the second electrode upon discharging the drop.

WO 2004/026582 A1